

LUX ELEMENTS®-DRY-DBDZM 100/150/200/380

Product Description

LUX ELEMENTS®-DRY-DBDZM is a sleeve which has been specially developed for the sealing of pipe ducts.

LUX ELEMENTS®-DRY-DBDZM has a flexible expansion zone for this application.

LUX ELEMENTS®-DRY-DBDZM is a system component of the LUX ELEMENTS®-ELEMENT-EL VK sealing system.

Technical data

	DBZM 100	DBZM 150	DBZM 200	DBZM 380
Colour	grey	grey	grey	grey
Material sealing layer	PVC	PVC	PVC	PVC
Material surface	PP tissue	PP tissue	PP tissue	PP tissue
Dimensions [mm]	100 x 100	150 x 150	200 x 200	380 x 380
Diameter of expansion zone [mm]	35	70	115	130
Hole diameter [mm]	8	18	65	40
Recommended for pipe diameter [mm]	10 – 20	22 – 42	70 – 100	42 – 85
Material thickness [mm]	0,9	0,9	0,9	0,9
Thermal resistance [°C]	-5/+60	-5/+60	-5/+60	-5/+60

Applications

Sealing pipe ducts with different diameters.

Substrate

Substrate requirements:

- clean, firm and even
- the substrate must correspond with the requirements of LUX ELEMENTS®-DRY-ASK

Recommended use

[see assembly instructions for LUX ELEMENTS®-ELEMENT-EL VK]

Characteristics

The LUX ELEMENTS®-DRY system products are waterproof and resistant against the usual chemical exposure that occurs during tile laying, according to their application. The fleece backed products are age resistant and do not rot.

Storage

Cool and dry, keep away from direct sunlight.

The relevant recommendations and guidelines, as well as DIN regulations, European standards and safety datasheets are to be observed. The recognised architectural and technical rules apply. We accept liability for the perfect quality of our products. Our processing recommendations are based upon trials and practical experience; they can, however, be no more than general instructions without assurance as to their quality, since we have no influence on the site conditions, on the execution of the work and the processing. With the issuing of this product datasheet previous versions cease to be valid.

LUX ELEMENTS GmbH & Co. KG

An der Schusterinsel 7
 D - 51379 Leverkusen-Opladen
 Tel. +49 (0) 21 71/72 12-0
 Fax +49 (0) 21 71/72 12-40
 E-Mail info@luxelements.de

LUX ELEMENTS S.A.S

31, rue d'Ensisheim
 F - 68190 Ungersheim
 Tél. +33 (0) 3 89 83 69 79
 Fax +33 (0) 3 89 48 83 27
 E-Mail info@luxelements.fr