

IAPMO RESEARCH AND TESTING, INC.

5001 East Philadelphia Street, Ontario, California 91761-2816 – USA • 909-472-4100 • 909-472-4244 • www.iapmort.org



CERTIFICATE OF LISTING

IAPMO Research and Testing, Inc. is a product certification body which tests and inspects samples taken from the supplier's stock or from the market or a combination of both to verify compliance to the requirements of applicable codes and standards. This activity is coupled with periodic surveillance of the supplier's factory and warehouses as well as the assessment of the supplier's Quality Assurance System. This listing is subject to the conditions set forth in the characteristics below and is not to be construed as any recommendation, assurance or guarantee by IAPMO Research and Testing, Inc. of the product acceptance by Authorities Having Jurisdiction.

The most updated information on this Certificate of Listing is available online at pld.iapmo.org

Effective Date: April 2017

Void After: April 2018

Product: Tileable Shower Receptors and Shower Kits

File No. 8712

Issued To: Lux Elements Gmbh & Co. Kg
An Der Schusterinsel 7
51379 Leverkusen,
Germany

Identification: Each tileable shower receptors and shower kit shall be clearly and permanently marked with the manufacturer's name or trademark, the model number, and all other required markings required by the standard. The product shall also bear the cUPC® certification mark.

Characteristics: To be installed in accordance with the manufacturer's instructions and the requirements of the latest edition of the Uniform Plumbing Code and National Plumbing Code of Canada

Products listed on this certificate have been tested by an IAPMO R&T recognized laboratory. This recognition has been granted based upon the laboratory's compliance to the applicable requirements of ISO/IEC 17025.

Products are in compliance with the following code(s):

Uniform Plumbing Code (UPC®)

National Plumbing Code of Canada


Chairman, Product Certification Committee


CEO, The IAPMO Group



This listing period is based upon the last date of the month indicated on the Effective Date and Void After Date shown above. Any change in material, manufacturing process, marking or design without having first obtained the approval of the Product Certification Committee, or any evidence of non-compliance with applicable codes and standards or of inferior workmanship, may be deemed sufficient cause for revocation of this listing. Production of or reference to this form for advertising purposes may be made only by specific written permission of IAPMO Research and Testing, Inc. Any alteration of this certificate could be grounds for revocation of the listing. This document shall be reproduced in its entirety.



IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

Page 2

Void After: April 2018

Product: Tileable Shower Receptors and Shower Kits

File No. 8712

Issued To: Lux Elements Gmbh & Co. Kg

Products are in compliance with the following standard(s):

IAPMO PS 106-2015e1



IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

Page 3

Void After: April 2018

Product: Tileable Shower Receptors and Shower Kits

File No. 8712

Issued To: Lux Elements GmbH & Co. Kg

MODELS:

TUB-XY- Point Drainage
TUB-LINE-YX - Line Drainage

TUB-HXY- Point Drainage
TUB-LINE-HYX - Line Drainage

Sizes: Width x Length x Height
750 to 2200 x 750 to 2200 x 35 to 55

If the dimensions are taller than 1800 x 900 the shower bases are supplied in two or more pieces.

H:
for the use on wooden sub-constructions; height of the tray 30 mm

TUB-BOL XY- Point Drainage
TUB-LINE-BOL YX - Line Drainage

BOL:
Square design with the sizes 1800x750x45 or 1800x900 x45
for replacement of bath tubs

X can be:
E = Drain outside the middle (for point drain)
M = Drain in the middle (for point drain)
1 = one sided gradient (for line drain)
4 = four sided gradient (for line drain)

Y can be:
Q = square design
F = Pentagon design
K = quadrant design
R = rectangular

Drainage System

| | |
|-------------------|------------------------|
| TUB-BA-S CST | Point drainage system |
| TUB LINE-BA-S CST | Linear drainage system |

Tileable Wall and Floor Panels

ELEMENT-EL
Sizes: Width x Length x Height
max. 600 x max. 2500 x 12 to 100
max. 1200 x max. 2600 x 12 to 49



IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

Page 4

Void After: April 2018

Product: Tileable Shower Receptors and Shower Kits

File No. 8712

Issued To: Lux Elements GmbH & Co. Kg

Adhesive
Col-MK

Note: Tileable Shower Trays with a slope between 2% and 4%.